




| Technical DATA SHEET | | | | |
|------------------------------------|-----------------------|--|----------------|-------------|
| Art FLOOR PRIME | | 8 MM - CLASS 32 - AC4 | | |
| THICKNESS | mm | 8 | EN 13329+A1 | |
| WIDTH | mm | 193 | EN 13329+A1 | |
| LENGHT | mm | 1205 | EN 13329+A1 | |
| SURFACE | | Impact | | |
| EUROPEAN STANDARD | - |    | EN 13329 | |
| PACKAGE DETAILS | | | | |
| PIECE | 8 piece / 1 package | | | |
| M ² | 1,86 m ² | | | |
| KG | 14 kg | | | |
| PALLET DETAILS | | | | |
| PIECE | 60 package / 1 pallet | | | |
| M ² | 111,66 m ² | | | |
| KG | 840 kg | | | |
| CLASS | - | 32 | EN 13329+A1 | |
| ABRASION RESISTANCE | - | AC4 | EN 13329+A1 | |
| THICKNESS SWELLING | % | ≤18 | ISO 24336 | |
| RESISTANCE TO IMPACT | SMALL BALL | N | ≥12 | EN 13329+A1 |
| | LARGE BALL | mm | ≥750 | |
| WARRANTY DOMESTIC / COMMERCIAL | Years | 15/10 | - | |
| RESISTANCE TO STAINING | - | Min. 5 (group 1 and 2) Min. 4 (group 3) | EN 438-2_5 | |
| SURFACE SOUNDNESS | N/mm ² | ≥1.25 | EN 13329+A1 | |
| LOCK STRENGTH | LENGHT | kN/m | f10,2 ≥ 1 | ISO 24334 |
| | WIDTH | kN/m | fs0,2 ≥ 2 | |
| EFFECT OF A CASTOR CHAIR | 25.000 Cycles | No Damage | EN 425:2002 | |
| EFFECT OF A FURNITURE LEG | - | No Damage | EN 424 | |
| OPENING BETWEEN ELEMENTS | mm | ≤0,20 | EN 13329+A1 | |
| HEIGHT DIFFERENCE BETWEEN ELEMENTS | mm | ≤0,15 | EN 13329+A1 | |
| MOISTURE CONTENT | % | 4-10 | EN 322 | |
| FIRE RESISTANCE | Class | C _s S1 | EN 9239-1 | |
| FORMALDEHYDE RELEASE | mg/m ² h | ≤3,5 (E1) | EN 12460-3 | |
| SLIP RESISTANCE | Class | DS | EN 13893:2003 | |
| IMPACT SOUND REDUCTION | dB | 14 | EN ISO 10140-3 | |
| THERMAL RESISTANCE | (m ² K)/W | 0,05 | EN 12664:2009 | |



Our products can also be produced with FSC® and CARB certification upon request.