



TECHNICAL DATA SHEET
Art FLOOR
 URBAN

8 MM - CLASS 32 - AC4

THICKNESS	mm	8	EN 13329+A2
WIDTH	mm	197	EN 13329+A2
LENGHT	mm	1205	EN 13329+A2
SURFACE		Authentic	
EUROPEAN STANDARD	-	 	EN 13329
PACKAGE DETAILS			
PIECE	8 pieces / 1 package		
M ²	1,899 m ²		
KG	13,8 kg		
PALLET DETAILS			
PIECE	60 packages / 1 pallet		
M ²	113,94 m ²		
KG	860 kg		
CLASS	-	32	EN 13329+A2
ABRASION RESISTANCE	-	AC4	EN 13329+A2
THICKNESS SWELLING	%	≤18	ISO 24336
SURFACE SWELLING (Assembled joint)	Qualitative Rating	Rating (1-5)	ISO 4760 (NALFA 24h)
	Quantitative Rating	mm	
RESISTANCE TO IMPACT	SMALL BALL	mm	EN 13329+A2
	LARGE BALL	mm	
WARRANTY DOMESTIC / COMMERCIAL	Years	15/10	-
RESISTANCE TO STAINING	-	Min. 5 (group 1 and 2) Min. 4 (group 3)	EN 438-2_5
SURCAFE SOUNDNESS	N/mm ²	≥1.25	EN 13329+A2
LOCK STRENGTH	LENGHT	kN/m	ISO 24334
	WIDTH	kN/m	
EFFECT OF A CASTOR CHAIR	25.000 Cycles	No Damage	EN 425:2002
EFFECT OF A FURNITURE LEG	-	No Damage	EN 424
OPENING BETWEEN ELEMENTS	mm	≤0,20	EN 13329+A2
HEIGHT DIFFERENCE BETWEEN ELEMENTS	mm	≤0,15	EN 13329+A2
MOISTURE CONTENT	%	4-10	EN 322
FIRE RESISTANCE	Class	C _f S1	EN 9239-1
FORMALDEHYDE RELEASE	mg/m ² h	≤3,5 (E1)	EN 12460-3
SLIP RESISTANCE	Class	DS	EN 14041:2008
THERMAL CONDUCTIVITY	W/(m*K)	0.148	EN 12667:2001
SOUND RATING	dB	14	ISO 717-2



Our products can also be produced with FSC® and CARB certification upon request.