



TECHNICAL DATA SHEET
Art FLOOR
WINGS

8 MM - CLASS 33 - AC5

| | | | |
|---|-----------------------|---|----------------------|
| THICKNESS | mm | 8 | EN 13329+A2 |
| WIDTH | mm | 197 | EN 13329+A2 |
| LENGHT | mm | 1205 | EN 13329+A2 |
| SURFACE | | Sky | |
| EUROPEAN STANDARD | - |   | EN 13329 |
| PACKAGE DETAILS | | | |
| PIECE | 8 piece / 1 package | | |
| Area (m ²) | 1,9 m ² | | |
| Weight (kg) | 14 kg | | |
| PALLET DETAILS | | | |
| PACKAGE | 56 package / 1 pallet | | |
| Area (m ²) | 106,4 m ² | | |
| Weight (kg) | 810 kg | | |
| CLASS | - | 33 | EN 13329+A2 |
| ABRASION RESISTANCE | - | AC5 | EN 13329+A2 |
| THICKNESS SWELLING | % | ≤15 | ISO 24336 |
| SURFACE SWELLING (Assembled joint) | Qualitative Rating | Rating (1-5) | ISO 4760 (NALFA 72h) |
| | Quantitative Rating | mm | |
| RESISTANCE TO IMPACT | SMALL BALL | N | EN 13329+A2 |
| | LARGE BALL | mm | |
| BODY VOLTAGE IN WALKING TEST (Antistatic Floor Covering) | kV | BV=0,9 | EN 1815:2016-09 |
| WARRANTY DOMESTIC / COMMERCIAL | Years | 25/15 | - |
| RESISTANCE TO STAINING | - | Min. 5 (group 1 and 2) Min. 4 (group 3) | EN 438-2_5 |
| SURFACE SOUNDNESS | N/mm ² | ≥1.25 | EN 13329+A2 |
| LOCK STRENGTH | LENGHT | kN/m | ISO 24334 |
| | WIDTH | kN/m | |
| EFFECT OF CASTOR CHAIR ^a | 25.000 Cycles | No Damage | EN 425:2002 |
| EFFECT OF A FURNITURE LEG | - | No Damage | EN 424 |
| OPENING BETWEEN ELEMENTS | mm | ≤0,20 | EN 13329+A2 |
| HEIGHT DIFFERENCE BETWEEN ELEMENTS | mm | ≤0,15 | EN 13329+A2 |
| MOISTURE CONTENT | % | 4-10 | EN 322 |
| FIRE RESISTANCE | Class | C _f S1 | EN 9239-1 |
| FORMALDEHYDE RELEASE | mg/m ² h | ≤3,5 (E1) | EN 12460-3 |
| SLIP RESISTANCE | Class | - | EN 13893:2003 |
| IMPACT SOUND REDUCTION | dB | 15 | EN ISO 10140-3 |
| THERMAL RESISTANCE | (m ² K)/W | 0,0614 | EN 12667:2001 |



Our products can also be produced with FSC® and CARB certification upon request.