

ICONIK 150

TECHNICAL DATA VINYL FLOORING 2020

Classification	Norm	Tarkett Value
Product type	EN ISO 26986	Expanded (cushioned) poly(vinyl chloride) floor covering
Domestic classification	EN ISO 10874	21 Domestic Moderate Light
Binder content	ISO 11638	Type I
Technical characteristics		
Total thickness	ISO 24346	1.5 mm
Wear layer thickness	ISO 24340	0,15 mm
Total weight	ISO 23997	1100 g/m ²
Roll Width		4 + 2 + 3 m
Roll Length	EN ISO 24341	35 m
Performance for CE Marking		
Declaration of Performance #	EN 14041	0007-0027-DOP-2020-01
Reaction to fire	EN 13501-1	Cfl-s1
Slip resistance	EN 13893 DIN 51130	≥ 0,50 (DS) R 9
Electrostatical propensity	EN 1815	≤ 2 kV
Thermal resistance (in m ² ·K/W)	ISO 10456 / EN 12524-1	0,02
Formaldehyde emission	EN 717-1	E1
Technical Performance		
Impact sound reduction - ΔLw	EN ISO 717-2	12 dB
Residual indentation	ISO 24343-1	≤ 0,20
Chemical resistance	ISO 26987	Not affected
Underfloor heating		Suitable (maximum 27°C)
Colour fastness to light	ISO 105-B02	≥ 6
Dimensional stability	ISO 23999	≤ 0,20 %
Sustainability, Environment & Indoor Air Quality		
Recyclable		Yes
French VOC rating		A+
Phthalate content		Phthalate-free
TVOC emissions after 28 days	EN 16516	Gold (≤ 100 µg / m ³)
Product ID		
Residential warranty (in years)		5
Surface treatment		Extreme Protection

The above information is subject to modification for the benefit of further improvement (2020-01).

